BookletChartTM


Parts of Coosaw and Broad Rivers NOAA Chart 11519



A reduced-scale NOAA nautical chart for small boaters When possible, use the full-size NOAA chart for navigation.



- Complete, reduced-scale nautical chart
- Print at home for free
- Convenient size
- Up-to-date with Notices to Mariners
- Compiled by NOAA's Office of Coast Survey, the nation's chartmaker



Published by the National Oceanic and Atmospheric Administration National Ocean Service Office of Coast Survey

<u>www.NauticalCharts.NOAA.gov</u> 888-990-NOAA

What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

What is a BookletChart[™]?

This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at http://www.NauticalCharts.NOAA.gov.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

Notice to Mariners Correction Status

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.

For latest Coast Pilot excerpt visit the Office of Coast Survey website at http://www.nauticalcharts.noaa.gov/nsd/searchbychart.php?chart=115 19.



(Selected Excerpts from Coast Pilot)
Combahee River, 3 miles above the mouth of the Coosaw River, had a reported controlling depth of 11.4 feet, in 2001, for a distance of about 9 miles above the entrance. The river is navigable for craft drawing up to 5 feet to U.S. Route 17 highway bridge 20 miles above the entrance. The highway bridge has a fixed span with a clearance of 14 feet. The mean range of tide is 6.4 feet at Fields Point, about 5.6 miles above the mouth of the

river, and 4.4 feet at the highway bridge.

New Chehaw River, on the north side of the entrance to Combahee River, is unimportant and has no traffic. **Old Chehaw River** enters the

Combahee River from northward about 2 miles above New Chehaw River. The town of **Wiggins** is about a mile above the junction of Old and New Chehaw Rivers.

Bull River enters Coosaw River from the northward about 5 miles above the latter's mouth. Two miles above its mouth, Bull River divides into **Williman Creek** and **Wimbee Creek**, which pass north and south, respectively, of **Williman Islands** and rejoin 4.5 miles above the lower junction. The upper section of Williman Creek where it rejoins Wimbee Creek is known as **Schooner Channel**.

Chisolm is a small town on the south bank of Wimbee Creek about 1.5 miles above the lower junction with Williman Creek. In 1983, the reported controlling depth to Chisolm was 8 feet. A section of a former railroad bridge, now used as a fishing pier, is on the west side of Wimbee Creek, 1 mile above the upper junction with Schooner Channel. An overhead power cable with a clearance of 80 feet crosses the creek at this point. In 1983, the reported controlling depth was 8 feet to the fishing pier by way of Bull River, Williman Creek, and Schooner Channel; between Chisolm and the upper junction with Schooner Channel, Wimbee Creek is nearly dry in places at low water.

Parrot Creek, which enters Coosaw River on the south side opposite Bull River, is a 2-mile link between Coosaw and Morgan Rivers. The reported controlling depth through the creek was 11 feet in 1994-1999.

Daybeacons mark the north entrance. In 1999, shoaling to bare was reported just NNW of Daybeacon 2 in the N entrance to Parrot Creek.

Lucy Point Creek, about 2 miles westward of Parrot Creek, also connects Coosaw and Morgan Rivers. In 1994-1999, the reported controlling depth in the creek was 8 feet, for about 0.3 mile. Currents in the creek are reported to be very changeable and unpredictable. A highway bridge crossing the creek 0.3 mile from the entrance has a fixed span with a clearance of 14 feet. The adjacent power and telephone cables have a clearance of 28 feet. There is a surfaced launching ramp close N of the fixed bridge. A daybeacon marks the entrance.

Morgan River flows into St. Helena Sound from westward. The river is about 8 miles long and at its head connects with Chowan Creek, a tributary of Beaufort River. At the divide, this passage is nearly dry at low water where U.S. Route 21 highway bridge has a 28-foot fixed span with a clearance of 4 feet. The mean range of tide near the head of Morgan River is about 7 feet. **Coffin Creek**, on the south side of Morgan River near the mouth, has a shrimp-packing plant 1.7 miles above the creek mouth. In 1985, the reported controlling depth was 2 feet across the bar at the mouth, thence 8 feet in midchannel to the plant. On Village Creek, about 0.8 mile above Coffin Creek, there are two shrimp-packing plants where diesel fuel and supplies may be obtained, in an emergency only. In 1985, using local knowledge, a reported depth of 5 feet was available from the entrance to the shrimp-packing plants 1.5 miles upstream. Edding Creek, is about 1.5 miles west of Village Creek. In 1983, the reported controlling depth in the creek was 5 feet for a distance of 2.5 miles.

On **Jenkins Creek**, about 2.1 miles westward of Edding Creek, are two shrimp-packing plants on the east side of the creek about 1.5 to 2 miles above the mouth. In 1994-1999, the reported controlling depth was 11 feet to these plants where diesel fuel, water and ice can be obtained. On the south shore of the Morgan River, west of Jenkins Creek, a marina has berths, electricity, gasoline, diesel fuel, water, ice, marine supplies, pump-out station, launching ramp and wet and dry storage. Hull, engine and electronic repairs can be made; a 50-ton lift is available.

U.S. Coast Guard Rescue Coordination Center 24 hour Regional Contact for Emergencies

RCC Miami Commander

7th CG District Miami, FL (305) 415-6800

2



NOAA's navigation managers serve as ambassadors to the maritime community.

They help identify navigational challenges facing professional and recreational mariners, and provide NOAA resources and information for safe navigation. For additional information, please visit nauticalcharts.noaa.gov/service/navmanagers

To make suggestions or ask questions online, go to *nauticalcharts.noaa.gov/inquiry*. To report a chart discrepancy, please use *ocsdata.ncd.noaa.gov/idrs/discrepancy.aspx*.

Lateral System As Seen Entering From Seaward on navigable waters except Western Rivers



CAUTION

Limitations on the use of radio signals as Limitations on the use of ractio signals a aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117. Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution. Station positions are shown thus:

Officurate location.

⊙(Accurate location) o(Approximate location)

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (foll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

CAUTION

SUBMARINE PIPELINES AND CABLES

Charted submarine pipelines and submarine cables and submarine pipeline and cable areas

^^^

Pipeline Area

Cable Area

Additional uncharted submarine pipelines and Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when archoring description, or vertically and control of the submarine the control of the

FISHING AND HUNT

Uncharted fish and w and structures such as crab traps, and duck blir may exist in the area of the near shore area. Ma with caution.

AIDS TO N

Consult U.S. Coas supplemental informati navigation.


SUPPLEMENTAL

Consult U.S. Coas supplemental informat

The prudent marine any single aid to navi floating aids. See U.S and U.S. Coast Pilot fo

anchoring, dragging, or trawling. Covered wells may be marked by lighted or unlighted buoys. SOUNDINGS IN FEET 51' 50' 49' 48′ ഗ \bigcirc 0 Gregorie Neck McKay Point 34' ഗ Brays Island 2 33' Hall Island Huguenins Neck 32' Deloss Island Ball Island Long Poi 31' Joins page 8

Note: Chart grid lines are aligned with true north.





THE NATION'S CHARTMAKER SINCE 1807

UNITED STATES - EAST COAST SOUTH CAROLINA

PARTS OF

COOSAW AND BROAD RIVERS

Mercator Projection Scale 1:40,000 at Lat. 32°30'

North American Datum of 1983 (World Geodetic System 1984) SOUNDINGS IN FEET AT MEAN LOWER LOW WATER

Formerly C&GS 794, 1st Ed., Jan 1937 C-1937-456 KAPP 222

ITING STRUCTURES vildlife harvesting devices s fish traps, pound nets, linds, some submerged, f this chart, particularly in Mariners should proceed

NAVIGATION

ast Guard Light List for ation concerning aids to

AL INFORMATION st Pilot 4 for important

NING

er will not rely solely on igation, particularly on 3. Coast Guard Light List r details.


RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

Charleston, SC KHB-29 162,550 MHz Savannah, GA Beaufort, SC KEC-85 WXJ-23 162.400 MHz 162.450 MHz Metter, GA WWH-25 162.425 MHz



This BookletChart was reduced to 75% of the original chart scale. The new scale is 1:53333. Barscales have also been reduced and are accurate when used to measure distances in this BookletChart.





THE NATION'S CHARTMAKER SINCE 1807

UNITED STATES - EAST COAST

SOUTH CAROLINA

PARTS OF

COOSAW AND BROAD RIVERS

Mercator Projection Scale 1:40,000 at Lat. 32°30'

North American Datum of 1983 (World Geodetic System 1984) SOUNDINGS IN FEET AT MEAN LOWER LOW WATER

HORIZONTAL DATUM

The horizontal reference datum of this chart is orth American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84), Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.678 northward and 0.622' eastward to agroe with his chart.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

HEIGHTS

Heights in feet above Mean High Water.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

CAUTION


Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

navigation in unknowr Charted reflect actu. navigation have been extinguish not rely up Wrecks up Wrecks up Mariner requested hazards to unit.

Hurrica

cause co

Navig Coast Pilo lished in t the regula mander, 7 Office of Charlesto Refer





Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

SCALE 1:40,000
Nautical Miles

See Note on page 5.

Yards

1000 0 1000 2000 3000 4000 5000

HUBBICANES AND TROPICAL STORMS

anes, tropical storms and other major storms may onsiderable damage to marine structures, aids to on and moored vessels, resulting in submerged debris wn locations. Id soundings, channel depths and shoreline may not

of soundings, channel depins and shortenine may not total conditions following these storms. Fixed aids to in may have been damaged or destroyed. Buoys may in moved from their charted positions, damaged, sunk, thed or otherwise made inoperative. Mariners should upon the position or operation of an aid to navigation. nd submerged obstructions may have been displaced ted locations. Pipelines may have become uncovered

ers are urged to exercise extreme caution and are ed to report aids to navigation discrepancies and to navigation to the nearest United States Coast Guard

NOTE A


NOTE A gation regulations are published in Chapter 2, U.S. lot 4. Additions or revisions to Chapter 2 are published Notice to Mariners. Information concerning lations may be obtained at the Office of the Com-7th Coast Guard District in Miami, FL or at the f the District Engineer, Corps of Engineers in on, SC.


to charted regulation section numbers

TIDAL INFORMATION


PLACE		Height referred to datum of soundings (MLLW)		
NAME	(LAT/LONG)	Mean Higher High Water	Mean High Water	Mean Low Water
		feet	feet	feet
Fields Point, Combahee River	(32°34'N/080°33'W)	6.8	6.4	0.2
Summerhouse Pt., Bull River	(32°31'N/080°34'W)	7.1	6.8	0.2
Brickyard Pt., Coosaw River	(32°29'N/080°41'W)	8.0	7.7	0.2
Coorning Landing, Whale Branch	(32°30'N/080°47'W)	8.6	8.2	0.2
Lucy Point Creek Entrance	(32°27'N/080°36'W)	6.7	6.4	0.1
Beaufort, Beaufort River	(32°26'N/080°40'W)	8.0	7.6	0.2

Dashes (- - -) located in datum columns indicate unavailable datum values for a tide station. Real-time water levels, tide predictions, and tidal current predictions are available on the Internet from http://tidesandcurrents.noaa.gov.





Last Correction: 4/29/2016. Cleared through: LNM: 2516 (6/21/2016), NM: 2716 (7/2/2016)





Printed at reduced scale.


Note: Chart grid lines are aligned with true north.


Printed at reduced scale.

SCALE 1:40,000
Nautical Miles

Yards

1000 0 1000 2000 3000 4000 5000





10


Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

SCALE 1:40,000
Nautical Miles

Yards

1000
0 1000 2000 3000 4000 5000





VHF Marine Radio channels for use on the waterways:

Channel 6 – Inter-ship safety communications.

Channel 9 – Communications between boats and ship-to-coast.

Channel 13 – Navigation purposes at bridges, locks, and harbors.

Channel 16 – Emergency, distress and safety calls to Coast Guard and others, and to initiate calls to other

vessels. Contact the other vessel, agree to another channel, and then switch.

Channel 22A – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here. Channels 68, 69, 71, 72 and 78A – Recreational boat channels.

Getting and Giving Help — Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.

Distress Call Procedures

- Make sure radio is on.
- Select Channel 16.
- Press/Hold the transmit button.
- Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of

Emergency; Number of People on Board.

- · Release transmit button.
- Wait for 10 seconds If no response Repeat MAYDAY call.

HAVE ALL PERSONS PUT ON LIFE JACKETS!



NOAA Weather Radio All Hazards (NWR) is a nationwide network of radio stations broadcasting continuous weather information directly from the nearest National Weather Service office. NWR broadcasts official Weather Service warnings, watches, forecasts and other hazard information 24 hours a day, 7 days a week.

http://www.nws.noaa.gov/nwr/

Quick References

Nautical chart related products and information — http://www.nauticalcharts.noaa.gov

Interactive chart catalog — http://www.charts.noaa.gov/InteractiveCatalog/nrnc.shtml

Report a chart discrepancy — http://ocsdata.ncd.noaa.gov/idrs/discrepancy.aspx

Chart and chart related inquiries and comments — http://ocsdata.ncd.noaa.gov/idrs/inquiry.aspx?frompage=ContactUs

Chart updates (LNM and NM corrections) — http://www.nauticalcharts.noaa.gov/mcd/updates/LNM_NM.html

Coast Pilot online — http://www.nauticalcharts.noaa.gov/nsd/cpdownload.htm

Tides and Currents — http://tidesandcurrents.noaa.gov

Marine Forecasts — http://www.nws.noaa.gov/om/marine/home.htm

National Data Buoy Center — http://www.ndbc.noaa.gov/

NowCoast web portal for coastal conditions — http://www.nowcoast.noaa.gov/

National Weather Service — http://www.weather.gov/

National Hurrican Center — http://www.nhc.noaa.gov/

Pacific Tsunami Warning Center — http://ptwc.weather.gov/

Contact Us — http://www.nauticalcharts.noaa.gov/staff/contact.htm



For the latest news from Coast Survey, follow @NOAAcharts



This Booklet chart has been designed for duplex printing (printed on front and back of one sheet). If a duplex option is not available on your printer, you may print each sheet and arrange them back-to-back to allow for the proper layout when viewing.